

Package: nflplotR (via r-universe)

July 23, 2024

Title NFL Logo Plots in 'ggplot2' and 'gt'

Version 1.3.1

Description A set of functions to visualize National Football League analysis in 'ggplot2' plots and 'gt' tables.

License MIT + file LICENSE

URL <https://nflplotr.nflverse.com>,

<https://github.com/nflverse/nflplotR>

BugReports <https://github.com/nflverse/nflplotR/issues>

Depends R (>= 3.5.0)

Imports cachem (>= 1.0.0), cli (>= 3.0.0), data.table (>= 1.14.0),
ggpath (>= 1.0.1), ggplot2 (>= 3.3.0), grid, gt (>= 0.8.0),
lifecycle, magick (>= 2.7.3), memoise (>= 2.0.0), nflreadr (>=
1.3.2), rappdirs (>= 0.3.0), rlang (>= 0.4.11), scales (>=
1.1.0)

Suggests base64enc (>= 0.1-3), covr, ggtext (>= 0.1.1), gridtext (>=
0.1.4), knitr, rmarkdown, rstudioapi (>= 0.13), rsvg (>= 2.0),
testthat (>= 3.0.0), vdiff (>= 1.0.2), webshot2 (>= 0.1.0)

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Repository <https://nflverse.r-universe.dev>

RemoteUrl <https://github.com/nflverse/nflplotR>

RemoteRef HEAD

RemoteSha 8547020cbc0c9f0489a59421d02057a45a4d8111

Contents

<code>.nflplotR_clear_cache</code>	2
<code>element</code>	3
<code>geom_from_path</code>	6
<code>geom_lines</code>	9
<code>geom_nfl_headshots</code>	11
<code>geom_nfl_logos</code>	14
<code>geom_nfl_wordmarks</code>	17
<code>ggpreview</code>	19
<code>gt_nfl_cols_label</code>	21
<code>gt_nfl_headshots</code>	23
<code>gt_nfl_logos</code>	24
<code>gt_render_image</code>	25
<code>nflverse_sitrep</code>	26
<code>nfl_team_factor</code>	27
<code>nfl_team_tiers</code>	28
<code>scale_nfl</code>	30
<code>valid_team_names</code>	33
Index	34

`.nflplotR_clear_cache` *Clear nflplotR Cache*

Description

This function clears the memoised cache of all functions memoised by `nflplotR`.

Usage

```
.nflplotR_clear_cache()
```

Value

Invisibly NULL

Examples

```
.nflplotR_clear_cache()
```

Description

In conjunction with the [ggplot2::theme](#) system, the following `element_` functions enable images in non-data components of the plot, e.g. axis text.

- `element_nfl_logo()`: draws NFL team logos instead of their abbreviations.
- `element_nfl_wordmark()`: draws NFL team wordmarks instead of their abbreviations.
- `element_nfl_headshot()`: draws NFL player headshots instead of their GSIS IDs.
- `element_path()`: draws images from valid image URLs instead of the URL.

Usage

```
element_nfl_logo(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)
```

```
element_nfl_wordmark(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)
```

```
element_nfl_headshot(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)
```

```
element_path(...)
```

Arguments

alpha	The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
colour, color	The image will be colorized with this color. Use the special character "b/w" to set it to black and white. For more information on valid color names in ggplot2 see https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill .
hjust, vjust	The horizontal and vertical adjustment respectively. Must be a numerical value between 0 and 1.
size	The output grob size in cm (!).
...	Arguments passed on to <code>ggpath::element_path</code>

Details

The elements translate NFL team abbreviations or NFL player GSIS IDs into logo images or player headshots, respectively.

Value

An S3 object of class `element`.

See Also

[geom_nfl_logos\(\)](#), [geom_nfl_headshots\(\)](#), [geom_nfl_wordmarks\(\)](#), and [geom_from_path\(\)](#) for more information on valid team abbreviations, player IDs, and other parameters.

The examples on <https://nflplotr.nflverse.com/articles/nflplotR.html>

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_logo())
```

```

# use logos for y-axis
ggplot(df, aes(y = teams, x = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.y = element_nfl_logo())

#####
# Headshot Examples
#####
library(nflplotR)
library(ggplot2)

# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)

dfh <- data.frame(
  random_value = runif(9, 0, 1),
  player_gsis = c("00-0033873",
                  "00-0026498",
                  "00-0035228",
                  "00-0031237",
                  "00-0036355",
                  "00-0019596",
                  "00-0033077",
                  "00-0012345",
                  "00-0031280")
)

# use headshots for x-axis
ggplot(dfh, aes(x = player_gsis, y = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_headshot(size = 1))

# use headshots for y-axis
ggplot(dfh, aes(y = player_gsis, x = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.y = element_nfl_headshot(size = 1))

# Restore old options
options(old)

#####
# Wordmarks and other Images
#####

library(ggplot2)

dt <- data.table::as.data.table(mtcars)[,
  `:=`(

```

```

team = sample(c("LAC", "BUF", "DAL", "ARI"), nrow(mtcars), TRUE),
player = sample(
  c("00-0033873", "00-0035228", "00-0036355", "00-0019596"),
  nrow(mtcars),
  TRUE
)
]

ggplot(dt, aes(x = mpg, y = disp)) +
  geom_point() +
  facet_wrap(vars(team)) +
  labs(
    title = tools::toTitleCase("These are random teams and data"),
    subtitle = "I just want to show how the nflplotR theme elements work",
    caption = "https://github.com/nflverse/nflseedR/raw/master/man/figures/caption.png"
  ) +
  theme_minimal() +
  theme(
    plot.title.position = "plot",
    plot.title = element_text(face = "bold"),
    axis.title = element_blank(),
    # make wordmarks of team abbreviations
    strip.text = element_nfl_wordmark(size = 1),
    # load image from url in caption
    plot.caption = element_path(hjust = 1, size = 0.4)
  )

```

geom_from_path

ggplot2 Layer for Visualizing Images from URLs or Local Paths

Description

This geom is used to plot images instead of points in a ggplot. It requires x, y aesthetics as well as a path. It has been outsourced to ggpath and is re-exported in nflplotR for compatibility reasons.

Usage

```
geom_from_path(...)
```

Arguments

... Arguments passed on to `ggpath::geom_from_path`

mapping Set of aesthetic mappings created by `aes()`. If specified and `inherit.aes = TRUE` (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.

- data** The data to be displayed in this layer. There are three options:
- If `NULL`, the default, the data is inherited from the plot data as specified in the call to `ggplot()`.
 - A `data.frame`, or other object, will override the plot data. All objects will be fortified to produce a data frame. See `fortify()` for which variables will be created.
 - A function will be called with a single argument, the plot data. The return value must be a `data.frame`, and will be used as the layer data. A function can be created from a formula (e.g. `~ head(.x, 10)`).
- stat** The statistical transformation to use on the data for this layer, either as a `ggproto` `Geom` subclass or as a string naming the stat stripped of the `stat_` prefix (e.g. "count" rather than "stat_count")
- position** Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use `position_jitter`), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
- na.rm** If `FALSE`, the default, missing values are removed with a warning. If `TRUE`, missing values are silently removed.
- show.legend** logical. Should this layer be included in the legends? `NA`, the default, includes if any aesthetics are mapped. `FALSE` never includes, and `TRUE` always includes. It can also be a named logical vector to finely select the aesthetics to display.
- inherit.aes** If `FALSE`, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. `borders()`.

Details

This function has been outsourced to the `ggpath` package. See `ggpath::geom_from_path` for details.

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_from_path()` understands the following aesthetics (required aesthetics have no default value):

- `x` The x-coordinate. Required.
- `y` The y-coordinate. Required.
- `path` a file path, url, raster object or bitmap array. See `magick::image_read()` for further information. Required.
- `alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in `ggplot2` see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

angle = 0 The angle of the image as a numerical value between 0° and 360°.

hjust = 0.5 The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

vjust = 0.5 The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

width = 1.0 The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is width = 0.1 (see below examples).

height = 1.0 The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is height = 0.1 (see below examples).

Examples

```
library(ggplot2)
library(nflplotR)

# create x-y-coordinates of a pentagon and add nflverse logo urls
df <- data.frame(
  a = c(sin(2 * pi * (0:4) / 5), 0),
  b = c(cos(2 * pi * (0:4) / 5), 0),
  url = c(
    "https://github.com/nflverse/nflfastR/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nflseedR/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nfl4th/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nflreadr/raw/main/data-raw/logo.svg",
    "https://github.com/nflverse/nflplotR/raw/main/man/figures/logo.png",
    "https://github.com/nflverse/nflverse/raw/main/man/figures/logo.png"
  )
)

# plot images directly from url
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15) +
  coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
  theme_void()

# plot images directly from url and apply transparency
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15, alpha = 0.5) +
  coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
  theme_void()

# It is also possible and recommended to use the underlying Geom inside a
# ggplot2 annotation
ggplot() +
  annotate(
    ggpath::GeomFromPath,
    x = 0,
    y = 0,
    path = "https://github.com/nflverse/nflplotR/raw/main/man/figures/logo.png",
```



```

    width = 0.4
  ) +
  theme_minimal()

```

 geom_lines

ggplot2 Layer for Horizontal and Vertical Reference Lines

Description

These geoms can be used to draw horizontal or vertical reference lines in a ggplot. They use the data in the aesthetics `x0` and `y0` to compute their median or mean and draw them as a line.

Usage

```

geom_median_lines(...)

geom_mean_lines(...)

```

Arguments

`...` Arguments passed on to `ggpath::geom_mean_lines`, `ggpath::geom_median_lines`

`mapping` Set of aesthetic mappings created by `aes()`.

`data` The data to be displayed in this layer. There are three options:
 If `NULL`, the default, the data is inherited from the plot data as specified in the call to `ggplot()`.
 A `data.frame`, or other object, will override the plot data. All objects will be fortified to produce a data frame. See `fortify()` for which variables will be created.
 A function will be called with a single argument, the plot data. The return value must be a `data.frame`, and will be used as the layer data. A function can be created from a formula (e.g. `~ head(.x, 10)`).

`na.rm` If `FALSE`, the default, missing values are removed with a warning. If `TRUE`, missing values are silently removed.

`show.legend` logical. Should this layer be included in the legends? `NA`, the default, includes if any aesthetics are mapped. `FALSE` never includes, and `TRUE` always includes. It can also be a named logical vector to finely select the aesthetics to display.

`inherit.aes` If `FALSE`, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behavior from the default plot specification.

Details

These functions have been outsourced to the `ggpath` package. See `ggpath::geom_median_lines` and `ggpath::geom_mean_lines` for details.

Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_median_lines()` and `geom_mean_lines()` understand the following aesthetics (at least one of the `x0` or `y0` aesthetics is required):

`x0` The variable for which to compute the median/mean that is drawn as vertical line.

`y0` The variable for which to compute the median/mean that is drawn as horizontal line.

`alpha = NA` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`color = "red"` The color of the drawn lines.

`linetype = 2` The linetype of the drawn lines.

`size = 0.5` The size of the drawn lines. Deprecated as of ggplot2 v3.4.0, use `linewidth` instead.

`linewidth = 0.5` The width of the drawn lines. Starting at ggplot2 v3.4.0.

See Also

The underlying ggplot2 geoms `geom_hline()` and `geom_vline()`

Examples

```
library(ggplot2)

# inherit top level aesthetics
ggplot(mtcars, aes(x = disp, y = mpg, y0 = mpg, x0 = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# draw horizontal line only
ggplot(mtcars, aes(x = disp, y = mpg, y0 = mpg)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# draw vertical line only
ggplot(mtcars, aes(x = disp, y = mpg, x0 = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# choose your own value
ggplot(mtcars, aes(x = disp, y = mpg)) +
  geom_point() +
  geom_median_lines(x0 = 400, y0 = 15) +
```

```
geom_mean_lines(x0 = 150, y0 = 30, color = "blue") +
  theme_minimal()
```

```
geom_nfl_headshots      ggplot2 Layer for Visualizing NFL Player Headshots
```

Description

This geom is used to plot NFL player headshots instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL player gsis id.

Usage

```
geom_nfl_headshots(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

Arguments

mapping	Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to ggplot() . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code>), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.

...	Other arguments passed on to <code>ggplot2::layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.
<code>na.rm</code>	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_headshots()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`player_gsis` The players' NFL gsis id. Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in `ggplot2` see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
library(nflplotR)
library(ggplot2)
# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)
```

```

df <- data.frame(
  a = rep(1:3, 3),
  b = sort(rep(1:3, 3), decreasing = TRUE),
  player_gsis = c("00-0033873",
                  "00-0026498",
                  "00-0035228",
                  "00-0031237",
                  "00-0036355",
                  "00-0019596",
                  "00-0033077",
                  "00-0012345",
                  "00-0031280"),
  player_name = c("P.Mahomes",
                  "M.Stafford",
                  "K.Murray",
                  "T.Bridgewater",
                  "J.Herbert",
                  "T.Brady",
                  "D.Prescott",
                  "Non.Match",
                  "D.Carr")
)

# set a custom fill colour for one player
df$colour <- ifelse(df$a == 2 & df$b == 2, NA, "b/w")

# scatterplot of the headshots
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis), height = 0.2) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply alpha as constant
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis), height = 0.2, alpha = 0.5) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply colour as an aesthetic
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis, colour = colour), height = 0.2) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  scale_colour_identity() +
  theme_void()

# Restore old options
options(old)

```

geom_nfl_logos

*ggplot2 Layer for Visualizing NFL Team Logos***Description**

This geom is used to plot NFL team and conference logos instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL team abbreviation. The latter can be checked with [valid_team_names\(\)](#).

Usage

```
geom_nfl_logos(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

Arguments

mapping	Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to ggplot() . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code>), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to ggplot2::layer() . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.

na.rm	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_logos()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`team_abbr` The team abbreviation. Should be one of `valid_team_names()`. The function tries to clean team names internally by calling `nflreadr::clean_team_abbrs()`. Note: "NFL", "AFC", "NFC" are valid abbreviations! Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]
```

```

df <- data.frame(
  a = rep(1:8, 4),
  b = sort(rep(1:4, 8), decreasing = TRUE),
  teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
# also set a custom fill colour for the non "A" teams
df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams, alpha = alpha), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_color_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams, alpha = alpha, colour = colour), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  scale_color_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.075, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# it's also possible to plot NFL and conference logos
dat <- data.frame(a = c(1.5, 1:2), b = c(1, 0, 0), teams = c("NFL", "AFC", "NFC"))
ggplot(dat, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.25) +
  coord_cartesian(xlim = c(0.5, 2.5), ylim = c(-0.75, 1.75)) +
  theme_void()

```

geom_nfl_wordmarks *ggplot2 Layer for Visualizing NFL Team Wordmarks*

Description

This geom is used to plot NFL team wordmarks instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL team abbreviation. The latter can be checked with `valid_team_names()`.

Usage

```
geom_nfl_wordmarks(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>aes()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to <code>ggplot()</code> . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code>), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to <code>ggplot2::layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.

na.rm	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_logos()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`team_abbr` The team abbreviation. Should be one of `valid_team_names()`. The function tries to clean team names internally by calling `nflreadr::clean_team_abbrs()`. Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in `ggplot2` see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.1` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
```

```

a = rep(1:8, 4),
b = sort(rep(1:4, 8), decreasing = TRUE),
teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
# also set a custom fill colour for the non "A" teams
df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all wordmarks
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams, alpha = alpha), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_color_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams, alpha = alpha, colour = colour), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  scale_alpha_identity() +
  scale_color_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams), width = 0.12, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  theme_void()

```

Description

This function previews a ggplot in its actual dimensions in order to see how it will look when saved. It is also significantly faster than the default preview in RStudio for ggplots created using `nlplotR`.

Usage

```
ggpreview(
  plot = ggplot2::last_plot(),
  width = NA,
  height = NA,
  asp = NULL,
  dpi = 300,
  device = "png",
  units = c("in", "cm", "mm", "px"),
  scale = 1,
  limitsize = TRUE,
  bg = NULL,
  ...
)
```

Arguments

<code>plot</code>	Plot to save, defaults to last plot displayed.
<code>width, height</code>	Plot size in units expressed by the <code>units</code> argument. If not supplied, uses the size of the current graphics device.
<code>asp</code>	The aspect ratio of the plot calculated as <code>width / height</code> . If this is a numeric value (and not <code>NULL</code>) the height of the plot will be recalculated to <code>height = width / asp</code> .
<code>dpi</code>	Plot resolution. Also accepts a string input: "retina" (320), "print" (300), or "screen" (72). Applies only to raster output types.
<code>device</code>	Device to use. Can either be a device function (e.g. png), or one of "eps", "ps", "tex" (pictex), "pdf", "jpeg", "tiff", "png", "bmp", "svg" or "wmf" (windows only). If <code>NULL</code> (default), the device is guessed based on the filename extension.
<code>units</code>	One of the following units in which the width and height arguments are expressed: "in", "cm", "mm" or "px".
<code>scale</code>	Multiplicative scaling factor.
<code>limitsize</code>	When <code>TRUE</code> (the default), <code>ggsave()</code> will not save images larger than 50x50 inches, to prevent the common error of specifying dimensions in pixels.
<code>bg</code>	Background colour. If <code>NULL</code> , uses the <code>plot.background</code> fill value from the plot theme.
<code>...</code>	Other arguments passed on to the graphics device function, as specified by device.

Value

No return value, called for side effects.

Examples

```

library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
# note that the plot is assigned to the object "p"
p <- ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_logo())

# preview p with defined width and aspect ratio (only available in RStudio)
if (rstudioapi::isAvailable()){
  ggpreview(p, width = 5, asp = 16/9)
}

```

gt_nfl_cols_label *Render Logos, Wordmarks, and Headshots in 'gt' Table Column Labels*

Description

Translate NFL team abbreviations into logos and wordmarks or NFL player gsis IDs to player headshots and render these images in column labels of 'gt' tables.

Usage

```

gt_nfl_cols_label(
  gt_object,
  columns = gt::everything(),
  ...,
  height = 30,
  type = c("logo", "wordmark", "headshot")
)

```

Arguments

gt_object	A table object that is created using the <code>gt::gt()</code> function.
columns	The columns for which the image translation should be applied. Argument has no effect if <code>locations</code> is not NULL.
...	Currently not in use
height	The absolute height (px) of the image in the table cell.
type	One of "logo", "wordmark", or "headshot" selecting whether to render a team's logo or wordmark image, or a player's headshot.

Value

An object of class `gt_tbl`.

Output of below example**See Also**

The article that describes how nflplotR works with the 'gt' package <https://nflplotr.nflverse.com/articles/gt.html>

The logo and wordmark rendering functions `gt_nfl_logos()` and `gt_nfl_wordmarks()`.

The player headshot rendering function `gt_nfl_headshots()`.

Examples

```
library(gt)
label_df <- data.frame(
  "00-0036355" = 1,
  "00-0033873" = 2,
  "LAC" = 11,
  "KC" = 12,
  check.names = FALSE
)

# create gt table and translate player IDs and team abbreviations
# into headshots, logos, and wordmarks
table <- gt::gt(label_df) %>%
  nflplotR::gt_nfl_cols_label(
    columns = gt::starts_with("00"),
    type = "headshot"
  ) %>%
  nflplotR::gt_nfl_cols_label("LAC", type = "wordmark") %>%
  nflplotR::gt_nfl_cols_label("KC", type = "logo")
```

gt_nfl_headshots *Render Player Headshots in 'gt' Tables*

Description

Translate NFL player gsis IDs to player headshots and render these images in html tables with the 'gt' package.

Usage

```
gt_nfl_headshots(gt_object, columns, height = 30, locations = NULL)
```

Arguments

gt_object	A table object that is created using the <code>gt::gt()</code> function.
columns	The columns for which the image translation should be applied. Argument has no effect if locations is not NULL.
height	The absolute height (px) of the image in the table cell.
locations	If NULL (the default), the function will render logos/wordmarks in argument columns. Otherwise, the cell or set of cells to be associated with the team name transformation. Only the <code>gt::cells_body()</code> , <code>gt::cells_stub()</code> , <code>gt::cells_column_labels()</code> , and <code>gt::cells_row_groups()</code> helper functions can be used here. We can enclose several of these calls within a <code>list()</code> if we wish to make the transformation happen at different locations.

Value

An object of class `gt_tbl`.

Output of below example

See Also

The logo and wordmark rendering functions `gt_nfl_logos()` and `gt_nfl_wordmarks()`.

Examples

```
library(nflplotR)
library(gt)
# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)
df <- data.frame(
  player_gsis = c("00-0033873",
                 "00-0026498",
                 "00-0035228",
                 "00-0031237",
```

```

      "00-0036355",
      "00-0019596",
      "00-0033077",
      "00-0012345",
      "00-0031280"),
  player_name = c("P.Mahomes",
                  "M.Stafford",
                  "K.Murray",
                  "T.Bridgewater",
                  "J.Herbert",
                  "T.Brady",
                  "D.Prescott",
                  "Non.Match",
                  "D.Carr")
)

# Replace player IDs with headshot images
table <- gt(df) %>%
  gt_nfl_headshots("player_gsis")

# Restore old options
options(old)

```

 gt_nfl_logos

Render Logos and Wordmarks in 'gt' Tables

Description

Translate NFL team abbreviations into logos and wordmarks and render these images in html tables with the 'gt' package.

Usage

```
gt_nfl_logos(gt_object, columns, height = 30, locations = NULL)
```

```
gt_nfl_wordmarks(gt_object, columns, height = 30, locations = NULL)
```

Arguments

gt_object	A table object that is created using the <code>gt::gt()</code> function.
columns	The columns for which the image translation should be applied. Argument has no effect if locations is not NULL.
height	The absolute height (px) of the image in the table cell.
locations	If NULL (the default), the function will render logos/wordmarks in argument columns. Otherwise, the cell or set of cells to be associated with the team name transformation. Only the <code>gt::cells_body()</code> , <code>gt::cells_stub()</code> , <code>gt::cells_column_labels()</code> , and <code>gt::cells_row_groups()</code> helper functions can be used here. We can enclose several of these calls within a <code>list()</code> if we wish to make the transformation happen at different locations.

Value

An object of class `gt_tbl`.

Output of below example**See Also**

The player headshot rendering function `gt_nfl_headshots()`.

The article that describes how `nflplotR` works with the 'gt' package <https://nflplotr.nflverse.com/articles/gt.html>

Examples

```
library(gt)
library(nflplotR)
teams <- valid_team_names()
# remove conference logos from this example
teams <- teams[!teams %in% c("AFC", "NFC", "NFL")]
# create dataframe with all 32 team names
df <- data.frame(
  team_a = head(teams, 16),
  logo_a = head(teams, 16),
  wordmark_a = head(teams, 16),
  team_b = tail(teams, 16),
  logo_b = tail(teams, 16),
  wordmark_b = tail(teams, 16)
)
# create gt table and translate team names to logo/wordmark images
table <- df %>%
  gt() %>%
  gt_nfl_logos(columns = gt::starts_with("logo")) %>%
  gt_nfl_wordmarks(columns = gt::starts_with("wordmark"))
```

`gt_render_image`*Render 'gt' Table to Temporary png File*

Description

Saves a `gt` table to a temporary `png` image file and uses `magick` to render tables in reproducible examples like `reprex::reprex()` or in package function examples (see details for further information).

Usage

```
gt_render_image(gt_tbl, ...)
```

Arguments

`gt_tbl` An object of class `gt_tbl` usually created by `gt::gt()`
`...` Arguments passed on to `webshot2::webshot()` and `par()`.

Details

Rendering `gt` tables in function examples is not trivial because of the behavior of an underlying dependency: `chromote`. It keeps a process running even if the `chromote` session is closed. Unfortunately, this causes R CMD Check errors related to open connections after example runs. The only way to avoid this is setting the environment variable `_R_CHECK_CONNECTIONS_LEFT_OPEN_` to `"true"`. How to do that depends on where and how developers check their package. A good way to prevent an example from being executed because the environment variable was not set can be taken from the source code of this function.

Value

Returns NULL invisibly.

Examples

```
tbl <- gt::gt_preview(mtcars)
gt_render_image(tbl)
```

`nflverse_sitrep` *Get a Situation Report on System, nflverse Package Versions and Dependencies*

Description

See `nflreadr::nflverse_sitrep` for details.

Value

Situation report of R and package/dependencies.

nfl_team_factor	<i>Create Ordered NFL Team Name Factor</i>
-----------------	--

Description

Create Ordered NFL Team Name Factor

Usage

```
nfl_team_factor(teams, ...)
```

Arguments

teams	A vector of NFL team abbreviations that should be included in <code>valid_team_names()</code> . The function tries to clean team names internally by calling <code>nflreadr::clean_team_abbrs()</code> .
...	One or more unquoted column names of <code>nflreadr::load_teams()</code> to sort by. If empty, the function will sort by division and nick name in ascending order. This is intended to be used for faceted plots where team wordmarks are used in strip texts, i.e. <code>element_nfl_wordmark()</code> . See examples for more details.

Value

Object of class "factor"

Examples

```
# unsorted vector including NFL team abbreviations
teams <- c("LAC", "LV", "CLE", "BAL", "DEN", "PIT", "CIN", "KC")

# defaults to sort by division and nick name in ascending order
nfl_team_factor(teams)

# can sort by every column in nflreadr::load_teams()
nfl_team_factor(teams, team_abbr)

# descending order by using base::rev()
nfl_team_factor(teams, rev(team_abbr))

##### HOW TO USE IN PRACTICE #####

library(ggplot2)
# load some sample data from the ggplot2 package
plot_data <- mpg
# add a new column by randomly sampling the above defined teams vector
plot_data$team <- sample(teams, nrow(mpg), replace = TRUE)

# Now we plot the data and facet by team abbreviation. ggplot automatically
# converts the team names to a factor and sorts it alphabetically
ggplot(plot_data, aes(displ, hwy)) +
```

```

geom_point() +
facet_wrap(~team, ncol = 4) +
theme_minimal()

# We'll change the order of facets by making another team name column and
# converting it to an ordered factor. Again, this defaults to sort by division
# and nick name in ascending order.
plot_data$ordered_team <- nfl_team_factor(sample(teams, nrow(mpg), replace = TRUE))

# Let's check how the facets are ordered now.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 4) +
  theme_minimal()

# The facet order looks weird because the defaults is meant to be used with
# NFL team wordmarks. So let's use the actual wordmarks and look at the result.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 4) +
  theme_minimal() +
  theme(strip.text = element_nfl_wordmark())

```

nfl_team_tiers

Create NFL Team Tiers

Description

This function sets up a ggplot to visualize NFL team tiers.

Usage

```

nfl_team_tiers(
  data,
  title = "NFL Team Tiers, 2021 as of Week 4",
  subtitle = "created with the #nflplotR Tiermaker",
  caption = NULL,
  tier_desc = c(`1` = "Super Bowl", `2` = "Very Good", `3` = "Medium", `4` = "Bad", `5` =
    "What are they doing?", `6` = "", `7` = ""),
  presort = FALSE,
  alpha = 0.8,
  width = 0.075,
  no_line_below_tier = NULL,
  deval = FALSE
)

```

Arguments

<code>data</code>	A data frame that has to include the variables <code>tier_no</code> (the number of the tier starting from the top tier no. 1) and <code>team_abbr</code> (the team abbreviation). <code>team_abbr</code> should be one of <code>valid_team_names()</code> and the function tries to clean team names internally by calling <code>nflreadr::clean_team_abbrs()</code> . If <code>data</code> includes the variable <code>tier_rank</code> , these ranks will be used within each tier. Otherwise, if <code>presort = FALSE</code> , the function will assume that <code>data</code> is already sorted and if <code>presort = TRUE</code> , teams will be sorted alphabetically within tiers.
<code>title</code>	The title of the plot. If <code>NULL</code> , it will be omitted.
<code>subtitle</code>	The subtitle of the plot. If <code>NULL</code> , it will be omitted.
<code>caption</code>	The caption of the plot. If <code>NULL</code> , it will be omitted.
<code>tier_desc</code>	A named vector consisting of the tier descriptions. The names must equal the tier numbers from <code>tier_no</code>
<code>presort</code>	If <code>FALSE</code> (the default) the function assumes that the teams are already sorted within the tiers. Will otherwise sort alphabetically.
<code>alpha</code>	The alpha channel of the logos, i.e. transparency level, as a numerical value between 0 and 1.
<code>width</code>	The desired width of the logo in npc (Normalised Parent Coordinates).
<code>no_line_below_tier</code>	Vector of tier numbers. The function won't draw tier separation lines below these tiers. This is intended to be used for tiers that shall be combined (see examples).
<code>devel</code>	Determines if logos shall be rendered. If <code>FALSE</code> (the default), logos will be rendered on each run. If <code>TRUE</code> the team abbreviations will be plotted instead of the logos. This is much faster and helps with the plot development.

Value

A plot object created with `ggplot2::ggplot()`.

Examples

```
library(ggplot2)
library(data.table)
teams <- nflplotR::valid_team_names()
# remove conference logos from this example
teams <- teams[!teams %in% c("AFC", "NFC", "NFL")]
teams <- sample(teams)

# Build the team tiers data
# This is completely random!
dt <- data.table::data.table(
  tier_no = sample(1:5, length(teams), replace = TRUE),
  team_abbr = teams
)[,tier_rank := sample(1:.N, .N), by = "tier_no"]

# Plot team tiers
```

```
nfl_team_tiers(dt)

# Create a combined tier which is useful for tiers with lots of teams that
# should be split up in two or more rows. This is done by setting an empty
# string for the tier 5 description and removing the tier separation line
# below tier number 4.
# This example also shows how to turn off the subtitle and add a caption
nfl_team_tiers(dt,
  subtitle = NULL,
  caption = "This is the caption",
  tier_desc = c("1" = "Super Bowl",
               "2" = "Very Good",
               "3" = "Medium",
               "4" = "A Combined Tier",
               "5" = ""),
  no_line_below_tier = 4)

# For the development of the tiers, it can be useful to turn off logo image
# rendering as this can take quite a long time. By setting `devel = TRUE`, the
# logo images are replaced by team abbreviations which is much faster
nfl_team_tiers(dt,
  tier_desc = c("1" = "Super Bowl",
               "2" = "Very Good",
               "3" = "",
               "4" = "A Combined Tier",
               "5" = ""),
  no_line_below_tier = c(2, 4),
  devel = TRUE)
```

scale_nfl

Scales for NFL Team Colors

Description

These functions map NFL team names to their team colors in color and fill aesthetics

Usage

```
scale_color_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)
```

```

scale_colour_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)

scale_fill_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "fill",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)

```

Arguments

<code>type</code>	One of "primary" or "secondary" to decide which colortype to use.
<code>values</code>	If NULL (the default) use the internal team color vectors. Otherwise a set of aesthetic values to map data values to. The values will be matched in order (usually alphabetical) with the limits of the scale, or with breaks if provided. If this is a named vector, then the values will be matched based on the names instead. Data values that don't match will be given <code>na.value</code> .
<code>...</code>	Arguments passed on to discrete_scale
<code>palette</code>	A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., scales::pal_hue()).
<code>limits</code>	One of: <ul style="list-style-type: none"> • NULL to use the default scale values • A character vector that defines possible values of the scale and their order • A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang lambda function notation.
<code>drop</code>	Should unused factor levels be omitted from the scale? The default, TRUE, uses the levels that appear in the data; FALSE uses all the levels in the factor.
<code>na.translate</code>	Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify <code>na.translate = FALSE</code> .

scale_name	[Deprecated] The name of the scale that should be used for error messages associated with this scale.
name	The name of the scale. Used as the axis or legend title. If <code>waiver()</code> , the default, the name of the scale is taken from the first mapping used for that aesthetic. If <code>NULL</code> , the legend title will be omitted.
labels	One of: <ul style="list-style-type: none"> • <code>NULL</code> for no labels • <code>waiver()</code> for the default labels computed by the transformation object • A character vector giving labels (must be same length as breaks) • An expression vector (must be the same length as breaks). See <code>?plot-math</code> for details. • A function that takes the breaks as input and returns labels as output. Also accepts <code>rlang</code> <code>lambda</code> function notation.
guide	A function used to create a guide or its name. See <code>guides()</code> for more information.
call	The call used to construct the scale for reporting messages.
super	The super class to use for the constructed scale
aesthetics	Character string or vector of character strings listing the name(s) of the aesthetic(s) that this scale works with. This can be useful, for example, to apply colour settings to the <code>colour</code> and <code>fill</code> aesthetics at the same time, via <code>aesthetics = c("colour", "fill")</code> .
breaks	One of: <ul style="list-style-type: none"> • <code>NULL</code> for no breaks • <code>waiver()</code> for the default breaks (the scale limits) • A character vector of breaks • A function that takes the limits as input and returns breaks as output
na.value	The aesthetic value to use for missing (NA) values
guide	A function used to create a guide or its name. If <code>NULL</code> (the default) no guide will be plotted for this scale. See <code>ggplot2::guides()</code> for more information.
alpha	Factor to modify color transparency via a call to <code>scales::alpha()</code> . If <code>NA</code> (the default) no transparency will be applied. Can also be a vector of alphas. All alpha levels must be in range <code>[0, 1]</code> .

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)
```



```
ggplot(df, aes(x = teams, y = random_value)) +  
  geom_col(aes(color = teams, fill = teams), width = 0.5) +  
  scale_color_nfl(type = "secondary") +  
  scale_fill_nfl(alpha = 0.4) +  
  theme_minimal() +  
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

valid_team_names

Output Valid NFL Team Abbreviations

Description

Output Valid NFL Team Abbreviations

Usage

```
valid_team_names(exclude_duplicates = TRUE)
```

Arguments

exclude_duplicates

If TRUE (the default) the list of valid team abbreviations will exclude duplicates related to franchises that have been moved

Value

A vector of type "character".

Examples

```
# List valid team abbreviations excluding duplicates  
valid_team_names()
```

```
# List valid team abbreviations excluding duplicates  
valid_team_names(exclude_duplicates = FALSE)
```

Index

`.nflplotR_clear_cache`, 2

`aes()`, 6, 9, 11, 14, 17

`borders()`, 7, 12, 15, 18

`discrete_scale`, 31

`element`, 3

`element_nfl_headshot` (`element`), 3

`element_nfl_logo` (`element`), 3

`element_nfl_wordmark` (`element`), 3

`element_path` (`element`), 3

`fortify()`, 7, 9, 11, 14, 17

`geom_from_path`, 6

`geom_from_path()`, 4

`geom_hline()`, 10

`geom_lines`, 9

`geom_mean_lines` (`geom_lines`), 9

`geom_median_lines` (`geom_lines`), 9

`geom_nfl_headshots`, 11

`geom_nfl_headshots()`, 4

`geom_nfl_logos`, 14

`geom_nfl_logos()`, 4

`geom_nfl_wordmarks`, 17

`geom_nfl_wordmarks()`, 4

`geom_vline()`, 10

`ggpath::element_path`, 4

`ggpath::geom_from_path`, 6, 7

`ggpath::geom_mean_lines`, 9

`ggpath::geom_median_lines`, 9

`ggplot()`, 7, 9, 11, 14, 17

`ggplot2::ggplot()`, 7, 10, 12, 15, 18, 29

`ggplot2::guides()`, 32

`ggplot2::layer()`, 7, 10, 12, 14, 15, 17, 18

`ggplot2::theme`, 3

`ggpreview`, 19

`gt::cells_body()`, 23, 24

`gt::cells_column_labels()`, 23, 24

`gt::cells_row_groups()`, 23, 24

`gt::cells_stub()`, 23, 24

`gt::gt()`, 22–24, 26

`gt_nfl_cols_label`, 21

`gt_nfl_headshots`, 23

`gt_nfl_headshots()`, 22, 25

`gt_nfl_logos`, 24

`gt_nfl_logos()`, 22, 23

`gt_nfl_wordmarks` (`gt_nfl_logos`), 24

`gt_nfl_wordmarks()`, 22, 23

`gt_render_image`, 25

`guides()`, 32

`lambda`, 31, 32

`magick::image_read()`, 7

`nfl_team_factor`, 27

`nfl_team_tiers`, 28

`nflreadr::clean_team_abbrs()`, 15, 18, 27, 29

`nflreadr::load_teams()`, 27

`nflreadr::nflverse_sitrep`, 26

`nflverse_sitrep`, 26

`par()`, 26

`png`, 20

`scale_color_nfl` (`scale_nfl`), 30

`scale_colour_nfl` (`scale_nfl`), 30

`scale_fill_nfl` (`scale_nfl`), 30

`scale_nfl`, 30

`scales::alpha()`, 32

`scales::pal_hue()`, 31

`valid_team_names`, 33

`valid_team_names()`, 14, 15, 17, 18, 27, 29

`webshot2::webshot()`, 26