

Package: nflplotR (via r-universe)

September 3, 2024

Title NFL Logo Plots in 'ggplot2' and 'gt'

Version 1.4.0

Description A set of functions to visualize National Football League analysis in 'ggplot2' plots and 'gt' tables.

License MIT + file LICENSE

URL <https://nflplotr.nflverse.com>,
<https://github.com/nflverse/nflplotR>

BugReports <https://github.com/nflverse/nflplotR/issues>

Depends R (>= 3.5.0)

Imports backports (>= 1.1.6), cachem (>= 1.0.0), cli (>= 3.0.0), data.table (>= 1.14.0), ggpath (>= 1.0.1), ggplot2 (>= 3.3.0), grid, gt (>= 0.8.0), lifecycle, magick (>= 2.7.3), memoise (>= 2.0.0), nflreadr (>= 1.3.2), rlang (>= 0.4.11), scales (>= 1.1.0)

Suggests base64enc (>= 0.1-3), covr, knitr, rmarkdown, rstudioapi (>= 0.13), rsvg (>= 2.0), testthat (>= 3.0.0), vdiff (>= 1.0.2), webshot2 (>= 0.1.0)

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Repository <https://nflverse.r-universe.dev>

RemoteUrl <https://github.com/nflverse/nflplotR>

RemoteRef HEAD

RemoteSha cb5a8f61d6af574f89c9a38afd283080ab740e30

Contents

| | |
|---------------------------------|-----------|
| .nflplotR_clear_cache | 2 |
| element | 3 |
| geom_from_path | 6 |
| geom_lines | 9 |
| geom_nfl_headshots | 11 |
| geom_nfl_logos | 14 |
| geom_nfl_wordmarks | 17 |
| ggpreview | 21 |
| gt_nfl_cols_label | 22 |
| gt_nfl_headshots | 24 |
| gt_nfl_logos | 25 |
| gt_render_image | 27 |
| nflverse_sitrep | 28 |
| nfl_team_factor | 28 |
| nfl_team_tiers | 29 |
| scale_nfl | 31 |
| valid_team_names | 34 |
| Index | 35 |

| | |
|-----------------------|-----------------------------|
| .nflplotR_clear_cache | <i>Clear nflplotR Cache</i> |
|-----------------------|-----------------------------|

Description

This function clears the memoised cache of all functions memoised by nflplotR.

Usage

```
.nflplotR_clear_cache()
```

Value

Invisibly NULL

Examples

```
.nflplotR_clear_cache()
```

Description

In conjunction with the [ggplot2::theme](#) system, the following `element_` functions enable images in non-data components of the plot, e.g. axis text.

- `element_nfl_logo()`: draws NFL team logos instead of their abbreviations.
- `element_nfl_wordmark()`: draws NFL team wordmarks instead of their abbreviations.
- `element_nfl_headshot()`: draws NFL player headshots instead of their GSIS IDs.
- `element_path()`: draws images from valid image URLs instead of the URL.

Usage

```
element_nfl_logo(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)  
  
element_nfl_wordmark(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)  
  
element_nfl_headshot(  
  alpha = NULL,  
  colour = NA,  
  hjust = NULL,  
  vjust = NULL,  
  color = NULL,  
  size = 0.5  
)  
  
element_path(...)
```

Arguments

| | |
|---------------|---|
| alpha | The alpha channel, i.e. transparency level, as a numerical value between 0 and 1. |
| colour, color | The image will be colorized with this color. Use the special character "b/w" to set it to black and white. For more information on valid color names in ggplot2 see https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill . |
| hjust, vjust | The horizontal and vertical adjustment respectively. Must be a numerical value between 0 and 1. |
| size | The output grob size in cm (!). |
| ... | Arguments passed on to <code>ggpath::element_path</code> |

Details

The elements translate NFL team abbreviations or NFL player GSIS IDs into logo images or player headshots, respectively.

Value

An S3 object of class `element`.

See Also

`geom_nfl_logos()`, `geom_nfl_headshots()`, `geom_nfl_wordmarks()`, and `geom_from_path()` for more information on valid team abbreviations, player IDs, and other parameters.

The examples on <https://nflplotr.nflverse.com/articles/nflplotR.html>

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_logo())
```

```

# use logos for y-axis
ggplot(df, aes(y = teams, x = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.y = element_nfl_logo())

#####
# Headshot Examples
#####
library(nflplotR)
library(ggplot2)

# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)

dfh <- data.frame(
  random_value = runif(9, 0, 1),
  player_gsis = c("00-0033873",
                  "00-0026498",
                  "00-0035228",
                  "00-0031237",
                  "00-0036355",
                  "00-0019596",
                  "00-0033077",
                  "00-0012345",
                  "00-0031280")
)

# use headshots for x-axis
ggplot(dfh, aes(x = player_gsis, y = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_headshot(size = 1))

# use headshots for y-axis
ggplot(dfh, aes(y = player_gsis, x = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.y = element_nfl_headshot(size = 1))

# Restore old options
options(old)

#####
# Wordmarks and other Images
#####

library(ggplot2)

dt <- data.table::as.data.table(mtcars)[,
  `:=`(

```

```

team = sample(c("LAC", "BUF", "DAL", "ARI"), nrow(mtcars), TRUE),
player = sample(
  c("00-0033873", "00-0035228", "00-0036355", "00-0019596"),
  nrow(mtcars),
  TRUE
)
)
]

ggplot(dt, aes(x = mpg, y = disp)) +
  geom_point() +
  facet_wrap(vars(team)) +
  labs(
    title = tools::toTitleCase("These are random teams and data"),
    subtitle = "I just want to show how the nflplotR theme elements work",
    caption = "https://github.com/nflverse/nflseedR/raw/master/man/figures/caption.png"
  ) +
  theme_minimal() +
  theme(
    plot.title.position = "plot",
    plot.title = element_text(face = "bold"),
    axis.title = element_blank(),
    # make wordmarks of team abbreviations
    strip.text = element_nfl_wordmark(size = 1),
    # load image from url in caption
    plot.caption = element_path(hjust = 1, size = 0.4)
  )

```

geom_from_path

ggplot2 Layer for Visualizing Images from URLs or Local Paths

Description

This geom is used to plot images instead of points in a ggplot. It requires x, y aesthetics as well as a path. It has been outsourced to ggpath and is re-exported in nflplotR for compatibility reasons.

Usage

```
geom_from_path(...)
```

Arguments

... Arguments passed on to [ggpath::geom_from_path](#)

mapping Set of aesthetic mappings created by [aes\(\)](#). If specified and `inherit.aes = TRUE` (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.

- data** The data to be displayed in this layer. There are three options:
- If `NULL`, the default, the data is inherited from the plot data as specified in the call to `ggplot()`.
 - A `data.frame`, or other object, will override the plot data. All objects will be fortified to produce a data frame. See `fortify()` for which variables will be created.
 - A function will be called with a single argument, the plot data. The return value must be a `data.frame`, and will be used as the layer data. A function can be created from a formula (e.g. `~ head(.x, 10)`).
- stat** The statistical transformation to use on the data for this layer. When using a `geom_*()` function to construct a layer, the `stat` argument can be used to override the default coupling between geoms and stats. The `stat` argument accepts the following:
- A `Stat` ggproto subclass, for example `StatCount`.
 - A string naming the stat. To give the stat as a string, strip the function name of the `stat_` prefix. For example, to use `stat_count()`, give the stat as `"count"`.
 - For more information and other ways to specify the stat, see the [layer stat](#) documentation.
- position** A position adjustment to use on the data for this layer. This can be used in various ways, including to prevent overplotting and improving the display. The `position` argument accepts the following:
- The result of calling a position function, such as `position_jitter()`. This method allows for passing extra arguments to the position.
 - A string naming the position adjustment. To give the position as a string, strip the function name of the `position_` prefix. For example, to use `position_jitter()`, give the position as `"jitter"`.
 - For more information and other ways to specify the position, see the [layer position](#) documentation.
- na.rm** If `FALSE`, the default, missing values are removed with a warning. If `TRUE`, missing values are silently removed.
- show.legend** logical. Should this layer be included in the legends? `NA`, the default, includes if any aesthetics are mapped. `FALSE` never includes, and `TRUE` always includes. It can also be a named logical vector to finely select the aesthetics to display.
- inherit.aes** If `FALSE`, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. `borders()`.

Details

This function has been outsourced to the `ggpath` package. See `ggpath::geom_from_path` for details.

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_from_path()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`path` a file path, url, raster object or bitmap array. See `magick::image_read()` for further information. Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.1` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
# example code
```

```
library(ggplot2)
library(nflplotR)

# create x-y-coordinates of a pentagon and add nflverse logo urls
df <- data.frame(
  a = c(sin(2 * pi * (0:4) / 5), 0),
  b = c(cos(2 * pi * (0:4) / 5), 0),
  url = c(
    "https://github.com/nflverse/nflfastR/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nflseedR/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nfl4th/raw/master/man/figures/logo.png",
    "https://github.com/nflverse/nflreadr/raw/main/data-raw/logo.svg",
    "https://github.com/nflverse/nflplotR/raw/main/man/figures/logo.png",
    "https://github.com/nflverse/nflverse/raw/main/man/figures/logo.png"
  )
)

# plot images directly from url
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15) +
```



```

coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
theme_void()

# plot images directly from url and apply transparency
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15, alpha = 0.5) +
  coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
  theme_void()

# It is also possible and recommended to use the underlying Geom inside a
# ggplot2 annotation
ggplot() +
  annotate(
    ggpath::GeomFromPath,
    x = 0,
    y = 0,
    path = "https://github.com/nflverse/nflplotR/raw/main/man/figures/logo.png",
    width = 0.4
  ) +
  theme_minimal()

```

geom_lines

ggplot2 Layer for Horizontal and Vertical Reference Lines

Description

These geoms can be used to draw horizontal or vertical reference lines in a ggplot. They use the data in the aesthetics `x0` and `y0` to compute their median or mean and draw them as a line.

Usage

```

geom_median_lines(...)

geom_mean_lines(...)

```

Arguments

... Arguments passed on to `ggpath::geom_mean_lines`, `ggpath::geom_median_lines`

mapping Set of aesthetic mappings created by `aes()`.

data The data to be displayed in this layer. There are three options:

- If `NULL`, the default, the data is inherited from the plot data as specified in the call to `ggplot()`.
- A `data.frame`, or other object, will override the plot data. All objects will be fortified to produce a data frame. See `fortify()` for which variables will be created.
- A function will be called with a single argument, the plot data. The return value must be a `data.frame`, and will be used as the layer data. A function can be created from a formula (e.g. `~ head(.x, 10)`).

`na.rm` If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.

`show.legend` logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.

`inherit.aes` If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behavior from the default plot specification.

Details

These functions have been outsourced to the `ggpath` package. See [ggpath::geom_median_lines](#) and [ggpath::geom_mean_lines](#) for details.

Value

A `ggplot2` layer ([ggplot2::layer\(\)](#)) that can be added to a plot created with [ggplot2::ggplot\(\)](#).

Aesthetics

`geom_median_lines()` and `geom_mean_lines()` understand the following aesthetics (at least one of the `x0` or `y0` aesthetics is required):

`x0` The variable for which to compute the median/mean that is drawn as vertical line.

`y0` The variable for which to compute the median/mean that is drawn as horizontal line.

`alpha = NA` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`color = "red"` The color of the drawn lines.

`linetype = 2` The linetype of the drawn lines.

`size = 0.5` The size of the drawn lines. Deprecated as of `ggplot2` v3.4.0, use `linewidth` instead.

`linewidth = 0.5` The width of the drawn lines. Starting at `ggplot2` v3.4.0.

See Also

The underlying `ggplot2` geoms [ggplot2::geom_hline](#) and [ggplot2::geom_vline](#)

Examples

```
library(ggplot2)

# inherit top level aesthetics
ggplot(mtcars, aes(x = disp, y = mpg, y0 = mpg, x0 = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# draw horizontal line only
ggplot(mtcars, aes(x = disp, y = mpg, y0 = mpg)) +
```

```

geom_point() +
geom_median_lines() +
geom_mean_lines(color = "blue") +
theme_minimal()

# draw vertical line only
ggplot(mtcars, aes(x = disp, y = mpg, x0 = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# choose your own value
ggplot(mtcars, aes(x = disp, y = mpg)) +
  geom_point() +
  geom_median_lines(x0 = 400, y0 = 15) +
  geom_mean_lines(x0 = 150, y0 = 30, color = "blue") +
  theme_minimal()

```

geom_nfl_headshots

*ggplot2 Layer for Visualizing NFL Player Headshots***Description**

This geom is used to plot NFL player headshots instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL player gsis id.

Usage

```

geom_nfl_headshots(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)

```

Arguments

| | |
|---------|--|
| mapping | Set of aesthetic mappings created by aes() . If specified and inherit.aes = TRUE (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | The data to be displayed in this layer. There are three options: If NULL, the default, the data is inherited from the plot data as specified in the call to ggplot() . |

| | |
|--------------------------|---|
| | <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p> |
| <code>stat</code> | <p>The statistical transformation to use on the data for this layer. When using a <code>geom_*()</code> function to construct a layer, the <code>stat</code> argument can be used to override the default coupling between geoms and stats. The <code>stat</code> argument accepts the following:</p> <ul style="list-style-type: none"> • A <code>Stat</code> ggproto subclass, for example <code>StatCount</code>. • A string naming the stat. To give the stat as a string, strip the function name of the <code>stat_</code> prefix. For example, to use <code>stat_count()</code>, give the stat as <code>"count"</code>. • For more information and other ways to specify the stat, see the layer stat documentation. |
| <code>position</code> | <p>A position adjustment to use on the data for this layer. This can be used in various ways, including to prevent overplotting and improving the display. The <code>position</code> argument accepts the following:</p> <ul style="list-style-type: none"> • The result of calling a position function, such as <code>position_jitter()</code>. This method allows for passing extra arguments to the position. • A string naming the position adjustment. To give the position as a string, strip the function name of the <code>position_</code> prefix. For example, to use <code>position_jitter()</code>, give the position as <code>"jitter"</code>. • For more information and other ways to specify the position, see the layer position documentation. |
| <code>...</code> | Other arguments passed on to <code>ggplot2::layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments. |
| <code>na.rm</code> | If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed. |
| <code>show.legend</code> | logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| <code>inherit.aes</code> | If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_headshots()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`player_gsis` The players' NFL gsis id. Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
library(nflplotR)
library(ggplot2)
# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)

df <- data.frame(
  a = rep(1:3, 3),
  b = sort(rep(1:3, 3), decreasing = TRUE),
  player_gsis = c("00-0033873",
                  "00-0026498",
                  "00-0035228",
                  "00-0031237",
                  "00-0036355",
                  "00-0019596",
                  "00-0033077",
                  "00-0012345",
                  "00-0031280"),
  player_name = c("P.Mahomes",
                  "M.Stafford",
                  "K.Murray",
                  "T.Bridgewater",
                  "J.Herbert",
                  "T.Brady",
                  "D.Prescott",
                  "Non.Match",
                  "D.Carr")
)
```

```

# set a custom fill colour for one player
df$colour <- ifelse(df$a == 2 & df$b == 2, NA, "b/w")

# scatterplot of the headshots
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis), height = 0.2) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply alpha as constant
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis), height = 0.2, alpha = 0.5) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply colour as an aesthetic
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_headshots(aes(player_gsis = player_gsis, colour = colour), height = 0.2) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  scale_colour_identity() +
  theme_void()

# Restore old options
options(old)

```

geom_nfl_logos

ggplot2 Layer for Visualizing NFL Team Logos

Description

This geom is used to plot NFL team and conference logos instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL team abbreviation. The latter can be checked with [valid_team_names\(\)](#).

Usage

```

geom_nfl_logos(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)

```

Arguments

| | |
|-------------|---|
| mapping | Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | <p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to ggplot().</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p> |
| stat | <p>The statistical transformation to use on the data for this layer. When using a <code>geom_*()</code> function to construct a layer, the <code>stat</code> argument can be used to override the default coupling between geoms and stats. The <code>stat</code> argument accepts the following:</p> <ul style="list-style-type: none"> • A <code>Stat</code> ggproto subclass, for example <code>StatCount</code>. • A string naming the stat. To give the stat as a string, strip the function name of the <code>stat_</code> prefix. For example, to use <code>stat_count()</code>, give the stat as <code>"count"</code>. • For more information and other ways to specify the stat, see the layer stat documentation. |
| position | <p>A position adjustment to use on the data for this layer. This can be used in various ways, including to prevent overplotting and improving the display. The <code>position</code> argument accepts the following:</p> <ul style="list-style-type: none"> • The result of calling a position function, such as <code>position_jitter()</code>. This method allows for passing extra arguments to the position. • A string naming the position adjustment. To give the position as a string, strip the function name of the <code>position_</code> prefix. For example, to use <code>position_jitter()</code>, give the position as <code>"jitter"</code>. • For more information and other ways to specify the position, see the layer position documentation. |
| ... | Other arguments passed on to ggplot2::layer() . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments. |
| na.rm | If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed. |
| show.legend | logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| inherit.aes | If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders() . |

Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_logos()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`team_abbr` The team abbreviation. Should be one of `valid_team_names()`. The function tries to clean team names internally by calling `nflreadr::clean_team_abbrs()`. Note: "NFL", "AFC", "NFC" are valid abbreviations! Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  a = rep(1:8, 4),
  b = sort(rep(1:4, 8), decreasing = TRUE),
  teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
# also set a custom fill colour for the non "A" teams
```



```

df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  expand_limits(y = c(0.9, 4.1)) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams, alpha = alpha), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  expand_limits(y = c(0.9, 4.1)) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_color_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams, alpha = alpha, colour = colour), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  expand_limits(y = c(0.9, 4.1)) +
  scale_alpha_identity() +
  scale_color_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.075, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  expand_limits(y = c(0.9, 4.1)) +
  theme_void()

# it's also possible to plot NFL and conference logos
dat <- data.frame(a = c(1.5, 1:2), b = c(1, 0, 0), teams = c("NFL", "AFC", "NFC"))
ggplot(dat, aes(x = a, y = b)) +
  geom_nfl_logos(aes(team_abbr = teams), width = 0.25) +
  coord_cartesian(xlim = c(0.5, 2.5), ylim = c(-0.75, 1.75)) +
  theme_void()

```

Description

This geom is used to plot NFL team wordmarks instead of points in a ggplot. It requires x, y aesthetics as well as a valid NFL team abbreviation. The latter can be checked with [valid_team_names\(\)](#).

Usage

```
geom_nfl_wordmarks(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

Arguments

- | | |
|----------|---|
| mapping | Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | <p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to ggplot().</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p> |
| stat | <p>The statistical transformation to use on the data for this layer. When using a <code>geom_*()</code> function to construct a layer, the <code>stat</code> argument can be used to override the default coupling between geoms and stats. The <code>stat</code> argument accepts the following:</p> <ul style="list-style-type: none"> • A Stat ggproto subclass, for example <code>StatCount</code>. • A string naming the stat. To give the stat as a string, strip the function name of the <code>stat_</code> prefix. For example, to use <code>stat_count()</code>, give the stat as <code>"count"</code>. • For more information and other ways to specify the stat, see the layer stat documentation. |
| position | <p>A position adjustment to use on the data for this layer. This can be used in various ways, including to prevent overplotting and improving the display. The <code>position</code> argument accepts the following:</p> <ul style="list-style-type: none"> • The result of calling a position function, such as <code>position_jitter()</code>. This method allows for passing extra arguments to the position. |

| | |
|--------------------------|---|
| | <ul style="list-style-type: none"> • A string naming the position adjustment. To give the position as a string, strip the function name of the <code>position_</code> prefix. For example, to use <code>position_jitter()</code>, give the position as "jitter". • For more information and other ways to specify the position, see the layer position documentation. |
| <code>...</code> | Other arguments passed on to <code>ggplot2::layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments. |
| <code>na.rm</code> | If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed. |
| <code>show.legend</code> | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| <code>inherit.aes</code> | If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |

Value

A `ggplot2` layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

Aesthetics

`geom_nfl_logos()` understands the following aesthetics (required aesthetics have no default value):

`x` The x-coordinate. Required.

`y` The y-coordinate. Required.

`team_abbr` The team abbreviation. Should be one of `valid_team_names()`. The function tries to clean team names internally by calling `nflreadr::clean_team_abbrs()`. Required.

`alpha = NULL` The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.

`colour = NULL` The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in `ggplot2` see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>

`angle = 0` The angle of the image as a numerical value between 0° and 360°.

`hjust = 0.5` The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.

`vjust = 0.5` The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.

`width = 1.0` The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.1` (see below examples).

`height = 1.0` The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

Examples

```

library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  a = rep(1:8, 4),
  b = sort(rep(1:4, 8), decreasing = TRUE),
  teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
# also set a custom fill colour for the non "A" teams
df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all wordmarks
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams, alpha = alpha), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_color_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams, alpha = alpha, colour = colour), width = 0.12) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +
  scale_x_continuous(expand = expansion(add = 0.5)) +
  scale_alpha_identity() +
  scale_color_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_nfl_wordmarks(aes(team_abbr = teams), width = 0.12, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.20, alpha = 0.5) +

```

```
scale_x_continuous(expand = expansion(add = 0.5)) +
theme_void()
```

ggpreview

Preview ggplot in Specified Dimensions

Description

This function previews a ggplot in its actual dimensions in order to see how it will look when saved. It is also significantly faster than the default preview in RStudio for ggplots created using `nfplotR`.

Usage

```
ggpreview(
  plot = ggplot2::last_plot(),
  width = NA,
  height = NA,
  asp = NULL,
  dpi = 300,
  device = "png",
  units = c("in", "cm", "mm", "px"),
  scale = 1,
  limitsize = TRUE,
  bg = NULL,
  ...
)
```

Arguments

| | |
|----------------------------|---|
| <code>plot</code> | Plot to save, defaults to last plot displayed. |
| <code>width, height</code> | Plot size in units expressed by the <code>units</code> argument. If not supplied, uses the size of the current graphics device. |
| <code>asp</code> | The aspect ratio of the plot calculated as <code>width / height</code> . If this is a numeric value (and not <code>NULL</code>) the height of the plot will be recalculated to <code>height = width / asp</code> . |
| <code>dpi</code> | Plot resolution. Also accepts a string input: "retina" (320), "print" (300), or "screen" (72). Applies only to raster output types. |
| <code>device</code> | Device to use. Can either be a device function (e.g. png), or one of "eps", "ps", "tex" (pictex), "pdf", "jpeg", "tiff", "png", "bmp", "svg" or "wmf" (windows only). If <code>NULL</code> (default), the device is guessed based on the filename extension. |
| <code>units</code> | One of the following units in which the width and height arguments are expressed: "in", "cm", "mm" or "px". |
| <code>scale</code> | Multiplicative scaling factor. |

| | |
|-----------|--|
| limitsize | When TRUE (the default), ggsave() will not save images larger than 50x50 inches, to prevent the common error of specifying dimensions in pixels. |
| bg | Background colour. If NULL, uses the plot.background fill value from the plot theme. |
| ... | Other arguments passed on to the graphics device function, as specified by device. |

Value

No return value, called for side effects.

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
# note that the plot is assigned to the object "p"
p <- ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_nfl_logo())

# preview p with defined width and aspect ratio (only available in RStudio)
if (rstudioapi::isAvailable()){
  ggpreview(p, width = 5, asp = 16/9)
}
```

| | |
|-------------------|---|
| gt_nfl_cols_label | <i>Render Logos, Wordmarks, and Headshots in 'gt' Table Column Labels</i> |
|-------------------|---|

Description

Translate NFL team abbreviations into logos and wordmarks or NFL player gsis IDs to player headshots and render these images in column labels of 'gt' tables.

Usage

```
gt_nfl_cols_label(
  gt_object,
  columns = gt::everything(),
  ...,
  height = 30,
  type = c("logo", "wordmark", "headshot")
)
```

Arguments

| | |
|-----------|---|
| gt_object | A table object that is created using the <code>gt::gt()</code> function. |
| columns | The columns for which the image translation should be applied. Argument has no effect if locations is not NULL. |
| ... | Currently not in use |
| height | The absolute height (px) of the image in the table cell. |
| type | One of "logo", "wordmark", or "headshot" selecting whether to render a team's logo or wordmark image, or a player's headshot. |

Value

An object of class `gt_tbl`.

Output of below example**See Also**

The article that describes how nflplotR works with the 'gt' package <https://nflplotr.nflverse.com/articles/gt.html>

The logo and wordmark rendering functions `gt_nfl_logos()` and `gt_nfl_wordmarks()`.

The player headshot rendering function `gt_nfl_headshots()`.

Examples

```
library(gt)
label_df <- data.frame(
  "00-0036355" = 1,
  "00-0033873" = 2,
  "LAC" = 11,
  "KC" = 12,
  check.names = FALSE
)

# create gt table and translate player IDs and team abbreviations
# into headshots, logos, and wordmarks
table <- gt::gt(label_df) %>%
```

```

nflplotR::gt_nfl_cols_label(
  columns = gt::starts_with("00"),
  type = "headshot"
) %>%
nflplotR::gt_nfl_cols_label("LAC", type = "wordmark") %>%
nflplotR::gt_nfl_cols_label("KC", type = "logo")

```

| | |
|------------------|---|
| gt_nfl_headshots | <i>Render Player Headshots in 'gt' Tables</i> |
|------------------|---|

Description

Translate NFL player gsis IDs to player headshots and render these images in html tables with the 'gt' package.

Usage

```
gt_nfl_headshots(gt_object, columns, height = 30, locations = NULL)
```

Arguments

| | |
|-----------|---|
| gt_object | A table object that is created using the gt::gt() function. |
| columns | The columns for which the image translation should be applied. Argument has no effect if locations is not NULL. |
| height | The absolute height (px) of the image in the table cell. |
| locations | If NULL (the default), the function will render logos/wordmarks in argument columns. Otherwise, the cell or set of cells to be associated with the team name transformation. Only the gt::cells_body() , gt::cells_stub() , gt::cells_column_labels() , and gt::cells_row_groups() helper functions can be used here. We can enclose several of these calls within a <code>list()</code> if we wish to make the transformation happen at different locations. |

Value

An object of class `gt_tbl`.

Output of below example

See Also

The logo and wordmark rendering functions [gt_nfl_logos\(\)](#) and [gt_nfl_wordmarks\(\)](#).

Examples

```

library(nflplotR)
library(gt)
# Silence an nflreadr message that is irrelevant here
old <- options(nflreadr.cache_warning = FALSE)
df <- data.frame(
  player_gsis = c("00-0033873",
                  "00-0026498",
                  "00-0035228",
                  "00-0031237",
                  "00-0036355",
                  "00-0019596",
                  "00-0033077",
                  "00-0012345",
                  "00-0031280"),
  player_name = c("P.Mahomes",
                  "M.Stafford",
                  "K.Murray",
                  "T.Bridgewater",
                  "J.Herbert",
                  "T.Brady",
                  "D.Prescott",
                  "Non.Match",
                  "D.Carr")
)

# Replace player IDs with headshot images
table <- gt(df) %>%
  gt_nfl_headshots("player_gsis")

# Restore old options
options(old)

```

gt_nfl_logos

*Render Logos and Wordmarks in 'gt' Tables***Description**

Translate NFL team abbreviations into logos and wordmarks and render these images in html tables with the 'gt' package.

Usage

```
gt_nfl_logos(gt_object, columns, height = 30, locations = NULL)
```

```
gt_nfl_wordmarks(gt_object, columns, height = 30, locations = NULL)
```

Arguments

| | |
|-----------|---|
| gt_object | A table object that is created using the <code>gt::gt()</code> function. |
| columns | The columns for which the image translation should be applied. Argument has no effect if <code>locations</code> is not NULL. |
| height | The absolute height (px) of the image in the table cell. |
| locations | If NULL (the default), the function will render logos/wordmarks in argument columns. Otherwise, the cell or set of cells to be associated with the team name transformation. Only the <code>gt::cells_body()</code> , <code>gt::cells_stub()</code> , <code>gt::cells_column_labels()</code> , and <code>gt::cells_row_groups()</code> helper functions can be used here. We can enclose several of these calls within a <code>list()</code> if we wish to make the transformation happen at different locations. |

Value

An object of class `gt_tbl`.

Output of below example**See Also**

The player headshot rendering function `gt_nfl_headshots()`.

The article that describes how nflplotR works with the 'gt' package <https://nflplotr.nflverse.com/articles/gt.html>

Examples

```
library(gt)
library(nflplotR)
teams <- valid_team_names()
# remove conference logos from this example
teams <- teams[!teams %in% c("AFC", "NFC", "NFL")]
# create dataframe with all 32 team names
df <- data.frame(
  team_a = head(teams, 16),
  logo_a = head(teams, 16),
  wordmark_a = head(teams, 16),
  team_b = tail(teams, 16),
  logo_b = tail(teams, 16),
  wordmark_b = tail(teams, 16)
)
# create gt table and translate team names to logo/wordmark images
table <- df %>%
  gt() %>%
  gt_nfl_logos(columns = gt::starts_with("logo")) %>%
  gt_nfl_wordmarks(columns = gt::starts_with("wordmark"))
```

| | |
|-----------------|---|
| gt_render_image | Render 'gt' Table to Temporary png File |
|-----------------|---|

Description

Saves a gt table to a temporary png image file and uses magick to render tables in reproducible examples like `reprex::reprex()` or in package function examples (see details for further information).

Usage

```
gt_render_image(gt_tbl, ...)
```

Arguments

| | |
|--------|--|
| gt_tbl | An object of class <code>gt_tbl</code> usually created by <code>gt::gt()</code> |
| ... | Arguments passed on to <code>webshot2::webshot()</code> and <code>par()</code> . |

Details

Rendering gt tables in function examples is not trivial because of the behavior of an underlying dependency: `chromote`. It keeps a process running even if the `chromote` session is closed. Unfortunately, this causes R CMD Check errors related to open connections after example runs. The only way to avoid this is setting the environment variable `_R_CHECK_CONNECTIONS_LEFT_OPEN_` to "false". How to do that depends on where and how developers check their package. A good way to prevent an example from being executed because the environment variable was not set to "false" can be taken from the source code of this function.

Value

Returns NULL invisibly.

Examples

```
tbl <- gt::gt_preview(mtcars)
gt_render_image(tbl)
```

| | |
|-----------------|---|
| nflverse_sitrep | <i>Get a Situation Report on System, nflverse Package Versions and Dependencies</i> |
|-----------------|---|

Description

See `nflreadr::nflverse_sitrep` for details.

Value

Situation report of R and package/dependencies.

| | |
|-----------------|--|
| nfl_team_factor | <i>Create Ordered NFL Team Name Factor</i> |
|-----------------|--|

Description

Create Ordered NFL Team Name Factor

Usage

```
nfl_team_factor(teams, ...)
```

Arguments

| | |
|-------|---|
| teams | A vector of NFL team abbreviations that should be included in <code>valid_team_names()</code> . The function tries to clean team names internally by calling <code>nflreadr::clean_team_abbrs()</code> . |
| ... | One or more unquoted column names of <code>nflreadr::load_teams()</code> to sort by. If empty, the function will sort by division and nick name in ascending order. This is intended to be used for faceted plots where team wordmarks are used in strip texts, i.e. <code>element_nfl_wordmark()</code> . See examples for more details. |

Value

Object of class "factor"

Examples

```
# unsorted vector including NFL team abbreviations
teams <- c("LAC", "LV", "CLE", "BAL", "DEN", "PIT", "CIN", "KC")

# defaults to sort by division and nick name in ascending order
nfl_team_factor(teams)

# can sort by every column in nflreadr::load_teams()
nfl_team_factor(teams, team_abbr)
```

```

# descending order by using base::rev()
nfl_team_factor(teams, rev(team_abbr))

##### HOW TO USE IN PRACTICE #####

library(ggplot2)
# load some sample data from the ggplot2 package
plot_data <- mpg
# add a new column by randomly sampling the above defined teams vector
plot_data$team <- sample(teams, nrow(mpg), replace = TRUE)

# Now we plot the data and facet by team abbreviation. ggplot automatically
# converts the team names to a factor and sorts it alphabetically
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~team, ncol = 4) +
  theme_minimal()

# We'll change the order of facets by making another team name column and
# converting it to an ordered factor. Again, this defaults to sort by division
# and nick name in ascending order.
plot_data$ordered_team <- nfl_team_factor(sample(teams, nrow(mpg), replace = TRUE))

# Let's check how the facets are ordered now.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 4) +
  theme_minimal()

# The facet order looks weird because the defaults is meant to be used with
# NFL team wordmarks. So let's use the actual wordmarks and look at the result.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 4) +
  theme_minimal() +
  theme(strip.text = element_nfl_wordmark())

```

nfl_team_tiers

Create NFL Team Tiers

Description

This function sets up a ggplot to visualize NFL team tiers.

Usage

```
nfl_team_tiers(
```

```

data,
title = "NFL Team Tiers, 2021 as of Week 4",
subtitle = "created with the #nflplotR Tiermaker",
caption = NULL,
tier_desc = c(`1` = "Super Bowl", `2` = "Very Good", `3` = "Medium", `4` = "Bad", `5` =
  "What are they doing?", `6` = "", `7` = ""),
presort = FALSE,
alpha = 0.8,
width = 0.075,
no_line_below_tier = NULL,
devel = FALSE
)

```

Arguments

| | |
|---------------------------------|---|
| <code>data</code> | A data frame that has to include the variables <code>tier_no</code> (the number of the tier starting from the top tier no. 1) and <code>team_abbr</code> (the team abbreviation). <code>team_abbr</code> should be one of <code>valid_team_names()</code> and the function tries to clean team names internally by calling <code>nflreadr::clean_team_abbrs()</code> . If data includes the variable <code>tier_rank</code> , these ranks will be used within each tier. Otherwise, if <code>presort = FALSE</code> , the function will assume that data is already sorted and if <code>presort = TRUE</code> , teams will be sorted alphabetically within tiers. |
| <code>title</code> | The title of the plot. If <code>NULL</code> , it will be omitted. |
| <code>subtitle</code> | The subtitle of the plot. If <code>NULL</code> , it will be omitted. |
| <code>caption</code> | The caption of the plot. If <code>NULL</code> , it will be omitted. |
| <code>tier_desc</code> | A named vector consisting of the tier descriptions. The names must equal the tier numbers from <code>tier_no</code> |
| <code>presort</code> | If <code>FALSE</code> (the default) the function assumes that the teams are already sorted within the tiers. Will otherwise sort alphabetically. |
| <code>alpha</code> | The alpha channel of the logos, i.e. transparency level, as a numerical value between 0 and 1. |
| <code>width</code> | The desired width of the logo in npc (Normalised Parent Coordinates). |
| <code>no_line_below_tier</code> | Vector of tier numbers. The function won't draw tier separation lines below these tiers. This is intended to be used for tiers that shall be combined (see examples). |
| <code>devel</code> | Determines if logos shall be rendered. If <code>FALSE</code> (the default), logos will be rendered on each run. If <code>TRUE</code> the team abbreviations will be plotted instead of the logos. This is much faster and helps with the plot development. |

Value

A plot object created with `ggplot2::ggplot()`.

Examples

```
library(ggplot2)
library(data.table)
teams <- nflplotR::valid_team_names()
# remove conference logos from this example
teams <- teams[!teams %in% c("AFC", "NFC", "NFL")]
teams <- sample(teams)

# Build the team tiers data
# This is completely random!
dt <- data.table::data.table(
  tier_no = sample(1:5, length(teams), replace = TRUE),
  team_abbr = teams
)[,tier_rank := sample(1:.N, .N), by = "tier_no"]

# Plot team tiers
nfl_team_tiers(dt)

# Create a combined tier which is useful for tiers with lots of teams that
# should be split up in two or more rows. This is done by setting an empty
# string for the tier 5 description and removing the tier separation line
# below tier number 4.
# This example also shows how to turn off the subtitle and add a caption
nfl_team_tiers(dt,
  subtitle = NULL,
  caption = "This is the caption",
  tier_desc = c("1" = "Super Bowl",
    "2" = "Very Good",
    "3" = "Medium",
    "4" = "A Combined Tier",
    "5" = ""),
  no_line_below_tier = 4)

# For the development of the tiers, it can be useful to turn off logo image
# rendering as this can take quite a long time. By setting `devel = TRUE`, the
# logo images are replaced by team abbreviations which is much faster
nfl_team_tiers(dt,
  tier_desc = c("1" = "Super Bowl",
    "2" = "Very Good",
    "3" = "",
    "4" = "A Combined Tier",
    "5" = ""),
  no_line_below_tier = c(2, 4),
  devel = TRUE)
```

Description

These functions map NFL team names to their team colors in color and fill aesthetics

Usage

```
scale_color_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)
```

```
scale_colour_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)
```

```
scale_fill_nfl(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "fill",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)
```

Arguments

| | |
|--------|--|
| type | One of "primary" or "secondary" to decide which colortype to use. |
| values | If NULL (the default) use the internal team color vectors. Otherwise a set of aesthetic values to map data values to. The values will be matched in order (usually alphabetical) with the limits of the scale, or with breaks if provided. If this is a named vector, then the values will be matched based on the names instead. Data values that don't match will be given na.value. |
| ... | Arguments passed on to discrete_scale |
| | limits One of: |

| | |
|------------|--|
| | <ul style="list-style-type: none"> • NULL to use the default scale values • A character vector that defines possible values of the scale and their order • A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang lambda function notation. |
| | <p>drop Should unused factor levels be omitted from the scale? The default, TRUE, uses the levels that appear in the data; FALSE includes the levels in the factor. Please note that to display every level in a legend, the layer should use <code>show.legend = TRUE</code>.</p> |
| | <p>na.translate Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify <code>na.translate = FALSE</code>.</p> |
| | <p>name The name of the scale. Used as the axis or legend title. If <code>waiver()</code>, the default, the name of the scale is taken from the first mapping used for that aesthetic. If NULL, the legend title will be omitted.</p> |
| | <p>labels One of:</p> <ul style="list-style-type: none"> • NULL for no labels • <code>waiver()</code> for the default labels computed by the transformation object • A character vector giving labels (must be same length as breaks) • An expression vector (must be the same length as breaks). See <code>?plot-math</code> for details. • A function that takes the breaks as input and returns labels as output. Also accepts rlang lambda function notation. |
| | <p>guide A function used to create a guide or its name. See guides() for more information.</p> |
| | <p>call The call used to construct the scale for reporting messages.</p> |
| | <p>super The super class to use for the constructed scale</p> |
| aesthetics | <p>Character string or vector of character strings listing the name(s) of the aesthetic(s) that this scale works with. This can be useful, for example, to apply colour settings to the colour and fill aesthetics at the same time, via <code>aesthetics = c("colour", "fill")</code>.</p> |
| breaks | <p>One of:</p> <ul style="list-style-type: none"> • NULL for no breaks • <code>waiver()</code> for the default breaks (the scale limits) • A character vector of breaks • A function that takes the limits as input and returns breaks as output |
| na.value | <p>The aesthetic value to use for missing (NA) values</p> |
| guide | <p>A function used to create a guide or its name. If NULL (the default) no guide will be plotted for this scale. See ggplot2::guides for more information.</p> |
| alpha | <p>Factor to modify color transparency via a call to scales::alpha. If NA (the default) no transparency will be applied. Can also be a vector of alphas. All alpha levels must be in range $[0, 1]$.</p> |

Examples

```
library(nflplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AFC", "NFC", "NFL")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)
ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_nfl(type = "secondary") +
  scale_fill_nfl(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

valid_team_names

Output Valid NFL Team Abbreviations

Description

Output Valid NFL Team Abbreviations

Usage

```
valid_team_names(exclude_duplicates = TRUE)
```

Arguments

exclude_duplicates

If TRUE (the default) the list of valid team abbreviations will exclude duplicates related to franchises that have been moved

Value

A vector of type "character".

Examples

```
# List valid team abbreviations excluding duplicates
valid_team_names()

# List valid team abbreviations excluding duplicates
valid_team_names(exclude_duplicates = FALSE)
```

Index

.nflplotR_clear_cache, 2

aes(), 6, 9, 11, 15, 18

borders(), 7, 12, 15, 19

discrete_scale, 32

element, 3

element_nfl_headshot(element), 3

element_nfl_logo(element), 3

element_nfl_wordmark(element), 3

element_path(element), 3

fortify(), 7, 9, 12, 15, 18

geom_from_path, 6

geom_from_path(), 4

geom_lines, 9

geom_mean_lines(geom_lines), 9

geom_median_lines(geom_lines), 9

geom_nfl_headshots, 11

geom_nfl_headshots(), 4

geom_nfl_logos, 14

geom_nfl_logos(), 4

geom_nfl_wordmarks, 17

geom_nfl_wordmarks(), 4

ggpath::element_path, 4

ggpath::geom_from_path, 6, 7

ggpath::geom_mean_lines, 9, 10

ggpath::geom_median_lines, 9, 10

ggplot(), 7, 9, 11, 15, 18

ggplot2::geom_hline, 10

ggplot2::geom_vline, 10

ggplot2::ggplot(), 7, 10, 12, 16, 19, 30

ggplot2::guides, 33

ggplot2::layer(), 7, 10, 12, 15, 16, 19

ggplot2::theme, 3

ggpreview, 21

gt::cells_body(), 24, 26

gt::cells_column_labels(), 24, 26

gt::cells_row_groups(), 24, 26

gt::cells_stub(), 24, 26

gt::gt(), 23, 24, 26, 27

gt_nfl_cols_label, 22

gt_nfl_headshots, 24

gt_nfl_headshots(), 23, 26

gt_nfl_logos, 25

gt_nfl_logos(), 23, 24

gt_nfl_wordmarks(gt_nfl_logos), 25

gt_nfl_wordmarks(), 23, 24

gt_render_image, 27

guides(), 33

lambda, 33

layer position, 7, 12, 15, 19

layer stat, 7, 12, 15, 18

magick::image_read(), 8

nfl_team_factor, 28

nfl_team_tiers, 29

nflreadr::clean_team_abbrs(), 16, 19, 28, 30

nflreadr::load_teams(), 28

nflreadr::nflverse_sitrep, 28

nflverse_sitrep, 28

par(), 27

png, 21

scale_color_nfl(scale_nfl), 31

scale_colour_nfl(scale_nfl), 31

scale_fill_nfl(scale_nfl), 31

scale_nfl, 31

scales::alpha, 33

valid_team_names, 34

valid_team_names(), 14, 16, 18, 19, 28, 30

webshot2::webshot(), 27